



C/I Medical Waste Series

Features:

- *Powered by the patented Thinline rack and pinion rotary actuator for smooth operation*
- *Available for domestic style 2-bar carts, European style carts and mobile trucks with bottom fork pockets*
- *Non-corrosive stainless steel chute to prevent spills*
- *230 & 460 volt 3-phase AC, 220 volt 1-phase AC and 12 volt DC self-contained hydraulic power units available*
- *Cycle times as low as 10 seconds*
- *Self-lubricating composite bearings at main main pivot points*
- *Powder coated finish for durability*

A Safe Solution for Transferring Medical Waste

Specifications:

Cart Compatibility:	C/I MWSVTL: ANSI Z245.60-1996 Type B Carts (Domestic style 2-Bar) C/I MWSEVTL: ANSI Z245.60-1996 Type C Carts (European Style) C/I MWDP-2: ANSI-Z245.60-1996 Type B Carts (Domestic style 2-Bar) 1 cubic yd Mobile Trucks (bottom fork pockets)
Lift Capacity:	C/I MWSVTL: 400 lbs @ 1800 psi (1100 actuator) C/I MWSEVTL: 400 lbs @ 1800 psi (1100 actuator) C/I MWDP-2: 1000 lbs @ 1800 psi (Dual 2200 actuator)
Voltage (60 Hz):	110/220 volt 1-phase AC 230/460 volt 3-phase AC 12 volt DC
Hydraulic Pressures:	Working Pressures: 1800 psi Maximum Pressures: 2500 psi
Hydraulic Flow:	0.5 gpm (110 volt 1-phase AC) 2.5 - 5.2 gpm (220 volt 1-phase AC, 230/460 volt 3-phase AC, 12 volt DC)
Cycle Time:	70 - 130 seconds (110 volt 1-phase AC) 10 - 12 seconds (220 volt 1-phase AC, 230/460 volt 3-phase AC, 12 volt DC)

Use them for loading waste into an incinerator, autoclave or rotoclave

Holtz Industries, Inc. • 200 South Terrace Court • Newark, OH 43055
Call Us Toll Free: 1-800-535-0104 • Local: 740-366-4002 • Fax: 740-366-0771