



C/I Taskmaster Series

Features:

- *Compatible with standard domestic style 2-bar roll-out carts*
- *Solid hook drive mechanism automatically secures the cart to the lift plate during the dump cycle*
- *230 and 460 volt 3-phase AC, 220 volt 1-phase AC and 12 volt DC self-contained hydraulic power units available*
- *Cycle times as low as 8 seconds*
- *Self-lubricating composite bearings at all pivot points eliminates the need for greasing*
- *Powder coated finish for durability*

**Combines the most advanced
Bayne cylinder lift products
mounted on rigid steel frames**

Specifications:

Cart Compatibility:

C/I TSKM: ANSI Z245.60-1996 Type B Carts (Domestic Style 2-Bar)

C/I HLIF: ANSI Z245.60-1996 Type B Carts (Domestic Style 2-Bar)

C/I SHLF: ANSI Z245.60-1996 Type B Carts (Domestic Style 2-Bar)

Tilt trucks with ANSI Standard 2-Bar Configuration-Up to 1 yard capacity

Lift Capacity:

C/I TSKM: 550 lbs @ 1800 psi

C/I HLIF: 750 lbs @ 1800 psi

C/I SHLF: 1000 lbw @ 1800 psi

Voltage (60 Hz):

230 and 460 volt 3-phase AC

220 volt 1-phase AC

12 volt DC

Hydraulic Pressures:

Working Pressures: 1800 psi

Maximum Pressures: 2500 psi

Hydraulic Flow:

2.5 gpm

Cycle Time:

8 - 10 seconds

Bearings:

Self-lubricating Composite Material

Finish:

Safety Yellow Powder Coating

**Units come standard with
hydraulic power unit and
electrical controls**

**Ideal for use on
Balers & Compactors**

Holtz Industries, Inc. • 200 South Terrace Court • Newark, OH 43055

Call Us Toll Free: 1-800-535-0104 • Local: 740-366-4002 • Fax: 740-366-0771