

D6098 Series Universal Auto-Arm



Perfect for the route that has a mix of carts, the Universal Auto-Arm will surpass all your expectations. Use it in parks, forests, alleys or anywhere that a wide variety of container types exist. Barrels? No problem!

Patented arm design hugs the lifter to maximize space savings when not in use.

Lifts virtually any container you can fit in it

Powerful 26k Helical Rotary Actuator

Available in 3 sizes for use on rearloaders, carry cans or sideloaders

Rubber strap / bumper array protects your containers.

2-year limited warranty



Model D6098, D6098-47 & D6098-51
An ISO 9001:2000 Company

HOLTZ 
INDUSTRIES, INC.

200 South Terrace Court
Newark, OH 43055
Phone: 1-800-535-0104
Web: www.holtzindustries.com

D6098, D6098-47 & D6098-51 Specifications



- 1 Lifts all ANSI Type G compatible carts, barrels, and variety of waste receptacles
- 2 Mounting height to top of plate:
D6098 39 1/2"
D6098-47 47"
D6098-51 51"
- 3 1,800-2,000 PSI required for 350lb load
- 4 6-8 second cycle time @ 3 GPM
- 5 45 degree dump angle
- 6 Safety Yellow powder-coated finish
- 7 Fiberglide bearings at pivot points
- 8 Easy bolt-on/off mounting plate offered at no charge, upon customer request
- 9 Arms fold away when not in use
- 10 Rubber bumpers/strap protect carts
- 11 Adjustable flow control valve
- 12 2 year limited warranty
- 13 Actuator produces 26k ft/lb of torque at 3,000 PSI
- 14 Internal roller bearings at each end for smooth operation
- 15 Shaft ends/matching hubs feature gear splines, not keyways, for superior torque transmission with low part stress
- 16 Extra-thick shaft handles heavy loads

HOLTZ 
INDUSTRIES, INC.

200 South Terrace Court
Newark, OH 43055
Phone: 1-800-535-0104
Web: www.holtzindustries.com

Specifications are subject to change without notice.