

Holtz Industries, Inc

O'Brian Tarper Systems-Get Yours Today



AutoCover II-C and AutoCover II-CH



AutoCover II-C: Heavy Duty streamline design features 3/16" thick wall, 2" wide rectangular steel tubing, 12" stroke upper cylinder

AutoCover II-CH: Extra Heavy Duty streamline design features 1/4" thick wall, 2" wide rectangular steel tubing, 24" stroke upper cylinder

Features:

- Large gussets re-designed for strength and stability
- Heavier arms for less maintenance and easier repair
- Roller spring is stronger, longer lasting
- Re-designed elbow for added strength to absorb shock (no welded angle that can crack & break)
- Rephasing cylinders
- Hydraulic hoses are routed inside arms for extra protection
- Covers load from 10 to 50 cubic yards
- Installed for 24' boxes and 16' box is locked 4 feet back
- Single joystick hydraulic control
- Hydraulic 1.8 gpm with a system pressure relief valve
- Tarp roller mounts to arm, rolls out over load
- Tarp made of 12 oz. polyester serim, extra durable 9' x 10' vinyl later at front edge for added reinforcement, memory flaps with webbing loops can be pulled over container and strapped down-standard tarp size is 9', 6' x 28'.

1-800-535-0104 or 1-800-499-7537