

# 4 Channel Mobile DVR

## 4 Channel Mobile DVR Part No: RC-DVR-MR4101



RC-DVR-MR4101

- H.264 standard compression algorithm, low bit rate, High picture quality.
- GPS information record.
- GPS timing function.
- Car fleet management on VMS.
- G-Sensor & events status record.
- Triple streaming - individual network video streaming, DVR record streaming and playback streaming.
- 3G phone remote view ( iPhone / iPad / Window Mobile / Android).
- HDD data retention days / Daylight saving time supported.
- Device ID setup for remote controller and control keyboard.
- DVR control: remote controller, mouse, control keyboard, network.
- Convenient backup by AVI file.
- USB firmware upgrade supported.
- Safari browser operation on MAC.
- Ignition-off record (30sec~60min).
- Vibration and shock proof.

### Specifications

| Model                 | RC-DVR-MR4101   |
|-----------------------|---|
| System                | PAL   |
| Video / Audio         | 4 CH input  |
| Video Output          | RCA x1  |
| Audio Output          | RCA x1  |
| S/N Ratio             | More than 40dB  |
| Color                 | 16.7 million  |
| Display Channel       | 1 / 2 / 3 / 4   |
| Display Resolution    | PAL :720(H) x 576(V)  |
| Display Rate          | 100 fps (PAL)   |
| Recording Resolution  | PAL :704 x 576 (D1)<br>PAL :704 x 288 (HD1)<br>PAL :352 x 288 (CIF)                         |
| Recording Rate        | PAL :704 x 576 (D1) 100 fps<br>PAL :704 x 288 (HD1) 100 fps<br>PAL :352 x 288 (CIF) 100 fps |
| Record Quality        | Highest / High / Normal / Low / Lowest  |
| Recording Mode        | Always / Event (Motion / Sensor / Speed (GPS) / G-Sensor) / Ignition-off                    |
| Playback Mode         | Date & Time search / Event search   |
| Multi-task            | Live / Record / Play / Network / Backup   |
| Motion Detect         | 45 x 30 grids camera for all channel  |
| Sensor (DI / DO)      | 8 Input / 1 Output  |
| RS485                 | PELCO-P / PELCO-D / Customized protocol   |
| Extend Indicator      | Optionl   |
| Backup                | USB 2.0 / Network remote backup   |
| Storage               | 2.5" SATA HDD x 1 ( Max : 2TB )   |
| HDD Record Mode       | Full stop / overwrite   |
| Language              | English / Chinese / Japanese / French / German / Portuguese                                 |
| Heater                | Optional  |
| Temperature Sensor    | Optional  |
| Mobile Surveillance   | iPhone / iPad / Window Mobile / Android   |
| IR Remote controller  | Standard  |
| GPS                   | Support NMEA 0183 protocol  |
| G-Sensor              | 3-axis  |
| 3G / 3.75G            | N/A   |
| Wi-Fi                 | N/A   |
| Ethernet              | 10/100/1000 M Base-T  |
| Network-Function      | Support licensed VMS(64CH) / IE browser   |
| Network Protocol      | TCP/IP, HTTP, DHCP, RTP, RTSP,SMTP  |
| Client Application    | Display / Playback / Backup / DVR control / PTZ Control / GPS / Google Map                  |
| Anti-vibration        | 1.5G 5~500Hz/ Random  |
| Shock proof           | Ready   |
| Power Source          | DC 9V~32V   |
| Operating Temperature | -20°C~55°C (-4°F~131°F); w/o heater:0°C~55°C  |
| Operating Humidity    | Less than 90%   |
| Dimension             | 224mm(W) x 62mm(H) x 197(D)mm   |

### Dimension Unit : mm

