

ETL-208 Series

Features:

- Powered by the patented Thinline rack and pinion rotary actuator for smooth operation
- Compatible with standard European style roll-out carts
- Sweeping motion allows for an increased cart pick-up envelope
- Thinline design works in conjunction with most commercial container latch kits
- Dumps cart higher and deeper inside the hopper opening to prevent spillage and increase route stops before cycling packer blade
- Self-lubricating composite bearings at all pivot points
- Powder-coated finish for durability

Specifications:

Cart Compatibility:	ANSI Z245-60-1996 Type C Carts European Style
Lift Capacity:	1100 Actuator 400 lbs @ 1800 psi (16", 20", 24" arms) 300 lbs @ 1800 psi (28", 32", 34" arms) 2200 Actuator 700 lbs @ 1800 psi (16", 20", 24" arms) 500 lbs @ 1800 psi (28", 32", 34" arms)
Hydraulic Pressures:	Working pressure: 1800 psi Maximum pressure: 2500 psi
Hydraulic Flow:	2.0-2.5 gpm



**For Rear Loaders
European Style Carts
Works With Container
Latch Kits**

NOTE:

1. DIMENSIONS ACCOMMODATE ANSI Z245.60-1996 TYPE C (EUROPEAN) CONTAINERS BUT MAY VARY DUE TO CONTAINER SPECIFICATIONS OR APPLICATIONS.
2. ALL DIMENSIONS ARE APPROXIMATE.
3. FOR BOLT-ON APPLICATIONS USE MOUNTING PLATE KIT 2000-1149.

