

ETL Series



Rear or Side Load

Features:

- Powered by the patented Thinline rack and pinion actuator for smooth operation
- Compatible with standard European style roll-out carts
- Dumps cart higher and deeper inside the hopper opening to prevent spillage and increase route stops before cycling packer blade
- Self-lubricating composite bearings at main pivot points
- Powder-coated finish for durability

Specifications:

Cart Compatibility:	ANSI Z245-60-1996 Type C Carts European Style
Lift Capacity:	1100 Actuator 400 lbs @ 1800 psi (16", 20", 24" arms) 300 lbs @ 1800 psi (28", 32", 34" arms) 2200 Actuator 700 lbs @ 1800 psi (16", 20", 24" arms) 500 lbs @ 1800 psi (28", 32", 34" arms)
Hydraulic Pressures:	Working pressure: 1800 psi Maximum pressure: 2500 psi
Hydraulic Flow:	2.0-2.5 gpm

Cycle Time:	6-8 seconds (lifter only) • 8-10 seconds (with 9" vertical) • 10-12 seconds (with 15" vertical) 15-25 seconds (with 24" or 34" vertical)
Bearings:	Self-lubricating Composite Material
Actuator:	Patented Thinline Rack and Pinion Rotary Actuator
Finish:	Safety Yellow Powder Coating

- NOTE:
1. DIMENSIONS ACCOMMODATE MOST ANSI Z245.60-1996 TYPE C (EUROPEAN) CONTAINERS, BUT MAY VARY DUE TO CONTAINER SPECIFICATIONS OR APPLICATIONS.
 2. ALL DIMENSIONS ARE APPROXIMATE.
 3. ETL UNITS WITH 20" OR LONGER ARMS REQUIRE A 4" MINIMUM OFFSET.
 4. UNITS MARKED WITH AN "*" HAVE A SLOW DOWN ACTUATOR.
 5. FOR BOLT-ON APPLICATIONS USE MOUNTING PLATE KIT 2000-1112.

