

Part No: RC-CC206FH

Works Only With:
RC-MC90LCD-Q4-SD (9" Monitor)
and RC-MC10LCD (10" Monitor)

Front Vision Camera



- Fixed lens for 2.1mm (up to 12mm)
- Build in microphone
- AHD2.0 / AHD3.0 compatible
- HD 720P
- Full HD

Specifications

Model	N/A	N/A	RC-CC206FH
Image Sensor	1/3" Image Sensor	1/3" Image Sensor	1/2.9" Image Sensor
Effective Pixel	756(H) x 504(V)	1280(H) x 960(V) approx. 1.27Mpixels	1985(H) x 1105(V) approx. 2.19M pixels
Dynamic Range	62.9 dB	82 dB	-
SNR	47.1 dB	44 dB	45 dB
HDR(WDR)	No		DWDR
Signal Sync	Internal Sync.	Internal Sync.	Internal Sync.
Video System	NTSC/PAL	AHD2.0	AHD2.0
Resolution	600 TV Line	720P	1080P
Output I/F	Composite 1.0 Vp-p / 75 ohm	Composite 1.0 Vp-p / 75 ohm	Composite 1.0 Vp-p / 75 ohm
Focal / F No.	2.1 mm/ F2.0	2.3mm/ F2.0	2.1mm/F:1.8
Lens Resolution	2M	2M	2M
View Angle (FOV)	H:139° V:78° D:160°	H:120° V:80° D:166°	H:150° V:80°
IR LED	No	No	NO
Audio in	Build in	Build in	Build in
Mirror	No	No	Option
Fish eye correction (de-warping)	No	No	NO
Voltage	DC12V ± 10%	DC12V ± 10%	DC12V ± 10%
Power consumption	1W(MAX)	1.2W(MAX)	1W(MAX)
Operation Temperature / Humidity	-20°C~70°C	-20°C~70°C	-20°C~70°C
Stock Temperature / Humidity	-40°C~85°C	-40°C~85°C	-40°C~80°C
Water-proof	NO	NO	NO
Vandal-proof	NO	NO	NO
Anti-vibration	ISO16750-3 4.1.3.2.3	ISO16750-3 4.1.3.2.3	ISO16750-3 4.1.3.2.3
Dimension	54.5mm(W) x 77.1mm(H) x 51.5mm(D)	54.5mm(W) x 77.1mm(H) x 51.5mm(D)	54.5mm(W) x 77.1mm(H) x 51.5mm(D)
Weight	NW:104g GW:140g	NW:104g GW:140g	NW:104g GW:140g
Connector	6 pin mini-din	6 pin mini-din	6 pin mini-din

